

IT-DUMPS Q&A

Accurate study guides, High passing rate!
IT-dumps provides update free of charge in one year!

Exam : **500-254**

Title : Implementing and
Configuring Cisco Identity
Service Engine - SISE

Version : Demo

1.Which two elements must you configure on a Cisco Wireless LAN Controller to allow Cisco ISE to authenticate wireless users? (Choose two.)

- A. Configure Cisco ISE as a RADIUS authentication server and enter a shared secret.
- B. Configure Cisco ISE as a RADIUS accounting server and enter a shared secret.
- C. Configure all attached LWAPs to use the configured Cisco ISE node.
- D. Configure RADIUS attributes for each SSID.
- E. Configure each WLAN to use the configured Cisco ISE node.
- F. Configure the Cisco Wireless LAN Controller to join a Microsoft Active Directory domain.

Answer: A,E

2.Which three Cisco TrustSec enforcement modes are used to help protect network operations when securing the network? (Choose three.)

- A. logging mode
- B. monitor mode
- C. semi-passive mode
- D. low-impact mode
- E. closed mode

Answer: B,D,E

3.Which statement is correct about Change of Authorization?

- A. Change of Authorization is a fundamental component of Cisco TrustSec and Cisco ISE.
- B. Change of Authorization can be triggered dynamically based on a matched condition in a policy, and manually by being invoked by an administrator operation.
- C. It is possible to trigger Change of Authorization manually from the ISE interface.
- D. Authentication is the supported Change of Authorization action type.

Answer: D

4.The default Cisco ISE node configuration has which role or roles enabled by default?

- A. Administration only
- B. Inline Posture only
- C. Administration and Policy Service
- D. Policy Service, Monitoring, and Administration

Answer: D

5.Inline Posture nodes support which enforcement mechanisms?

- A. VLAN assignment
- B. downloadable ACLs
- C. security group access
- D. dynamic ACLs

Answer: B