

Exam : 642-062

Title : Routing and Switching

Solutions for System

**Engineers** 

Version: Demo

1. Which two of these are features of the Cisco 2851 Integrated Services Router, but not features of Cisco 1800 Series Integrated Services Routers? (Choose two.)

Select 2 response(s).

- A. 32-Gbps switching bus
- B. built-in wireless module
- C. Cisco SDM for simplified management
- D. two integrated 10/100/1000 Ethernet ports
- E. Power over Ethernet support for 10/100 Ethernet ports
- F. slots dedicated to Cisco High-Density Analog and Digital Extension Module for Voice and Fax

Answer: DF

- 2. Which two of these features can be managed by the Cisco SDM application? (Choose two.) Select 2 response(s).
- A. VoIP
- B. HSRP
- C. IPsec VPN
- D. QoS policy
- E. PoE power consumption

Answer: CD

3. Your network includes a Cisco Catalyst 6500 Switch with an FWSM module. You need Layer 2 connectivity between two routers located on different firewall interfaces. Which feature will you need in order to provide this connectivity?

Select the best response.

- A. router mode
- B. virtual firewall
- C. stateful firewall
- D. transparent mode
- E. two FWSM modules in failover mode

Answer: D

4. Which supervisor module can be used in the Cisco Catalyst 4510R chassis?

Select the best response.

- A. Supervisor II-Plus
- B. Supervisor IV
- C. Supervisor V-10GE
- D. Supervisor II-TS

Answer: C

5. Which two tools can you use to manage and configure a Cisco Catalyst Express 500 Series Switch? (Choose two.)

Select 2 response(s).

- A. CLI
- B. Cisco Network Assistant

- C. Cisco Smartports Advisor
- D. Device Manager with embedded GUI

Answer: BD