

IT-DUMPS Q&A

Accurate study guides, High passing rate!
IT-dumps provides update free of charge in one year!

Exam : **642-979**

Title : Cisco Data Unified
Computing Support
Specialist Qualifier Exam

Version : Demo

1.Which two Cisco MDS features allow fabric-wide-consistent and VSAN-independent configurations of the zoning information? (Choose two)

- A. CFS
- B. sWWN
- C. Fibre Channel alias
- D. Device alias
- E. Interface ID
- F. port-based zoning

Answer: A,D

2.For purposes of granting restricted access to statically configure iSCSI virtual targets, when three of these can be used to identify iSCSI.? (Choose three)

- A. iSCSI node name
- B. hostname
- C. IPv4 address and subnet
- D. MAC address
- E. IPv6 address

Answer: A,C,E

3.You have been asked to configure a port on your Cisco MDS switch so that a host can join your fabric. Which of these port types should the port be set to?

- A. N_Port
- B. NL_Port
- C. F_Port
- D. E_Port
- E. TE_Port
- F. SD_Port

Answer: C

4.The customer is concerned with the current FCIP deployment because the FCIP tunnels are traversing the public IP infrastructure. To mitigate this issue the customer has decided to deploy Ipsec on the Cisco MDS 9Wi Switches that are used FCIP connectivity what additional license must be installed on the CISCO MDS 9222 switches?

- A. enterprise license
- B. Security license
- C. No additional license is required
- D. SAN extension license

Answer: A

5.Which interface should be used to configure VLANIDs and ACLs in an FcoF adapter of the Cisco Nexus 5000 switch?

- A. SV1
- B. virtual Fibre Channel
- C. virtual Ethernet

D. virtual interface group

Answer: C