

Exam : 642-982

Title : Cisco Data Center Unified

Computing Design

Specialist

Version: Demo

- 1. What are three features of the components that make up Cisco Datacenter 3.0? (Choose three.)
- A. Virtual Machines
- B. Virtualized Storage
- C. Security Manager
- D. Consolidated Connectivity
- E. Desktop Consolidator

Answer: A,B,D

- 2. Which design criteria would be considered environmental criteria.?
- A. improve security
- B. simplify system cabling
- C. reduce management effort
- D. simplify the data center architecture

Answer: B

- 3. What two key network aspects are attained when implementing a Cisco Data Center Computing Solution?(Choose two.)
- A. throughput
- B. storage capacity
- C. high availability
- D. cable management

Answer: A,C

- 4.which two expansion modules does the UCS 6120 Fabric Interconnect support?(Choose two.)
- A. Ethernet 10 GE(6polt)
- B. Ethernet 1 GE(6polt)
- C. Fibre Channel 1,2 and 4 Gbps I (8 port)
- D. Fibre Channel 1,2,4, and 8 Gbps(8 port)}

Answer: A,C

- 5. High availability in Cisco Data center Networking is implemented using which two techniques? (Choose two)
- A. Extended Spanning Tree Protocol
- B. Virtual Router Redundancy Protocol
- C. Cisco Datacenter Redundancy Protocol
- D. High availability module of the NX-operating system

Answer: A.B

- 6. The Cisco Unified computing solution provides which three advantages? (Choose three.)
- A. use of Private VDANs
- B. server statelessness
- C. higher memory capacity
- D. use of industry standard servers

Answer: B,C,D

- 7. Which four products are included in the Cisco Datacenter 3.0 portfolio? (Choose 4) A. ASA 5500
- B. Nexus 1000v
- C. Catalyst 3560
- D. MDS 9500
- E. UCS Manager
- F. UCS 6100 Fabric Interconnect

Answer: B,D,E,F

- 8. Which statement is true regarding UCS ports dedicated as external LAN device uplinks?
- A. Ports carry VLAN traffic only
- B. Ports are configured as ISL trunks
- C. Spanning tree must be enabled on these ports
- D. Ports are configured as access ports

Answer: C

- 9. Which of the following design criteria would be considered technical criteria?
- A. increase computing density
- B. simplify the data center architecture
- C. decrease security requirements through virtualization
- D. reduce power while increasing computing capacity

Answer: B

- 10. Which two design considerations are most often used when deploying Virtual Machines on the Cisco Sytems Nexus 1000V?(Choose two.)
- A. VSANs to be supported must be configured in the Fabric Manager on the MDS switches
- B. The default VSAN is preconfigured in the Cisco UCS manager.
- C. The default VSAN is chosen as the default connectivity for all vNlCs
- D. All VSANs In heterogeneous fabrics are used internally by the Cisco UCS system

Answer: B,D