

IT-DUMPS Q&A

Accurate study guides, High passing rate!
IT-dumps provides update free of charge in one year!

Exam : **C2180-175**

Title : IBM WebSphere Lombardi
Edition V7.2, Development
(Entry)

Version : Demo

1.What is the correct JavaScript syntax to initialize a local variable named contact of a complex type Contact?

- A. `contact = new Contact();`
- B. `tw.local.contact = new Contact();`
- C. `tw.local.contact = new tw.local.Contact();`
- D. `tw.local.contact = new tw.object.Contact();`

Answer: D

2.The service "Get Request ID" needs to know the number of existing requests of a particular type in order to generate an ID for the request. It uses a nested service named "Get Request Count" for this purpose. What can be determined about data mapping. ?

- A. The type of the request is an output variable of the 'Get Request ID' service.
- B. The unique ID for the request is an input variable to the 'Get Request ID' service.
- C. The number of existing requests of a particular type is an input variable to the 'Get Request Count' service.
- D. The 'Get Request ID' service has a private variable that maps to the output from 'Get Request Count' service.

Answer: D

3.An application has five pieces of data: `creditScore`, `newHomeAddress`, `amountToBorrow`, `creditApproved`, and `appraisalPassed`. The data is organized in a complex variable, `loanApp`. How should the developer reference the credit score?

- A. `tw.local.creditScore`
- B. `tw.loanApp.creditScore`
- C. `tw.local.loanApp.creditScore`
- D. `tw.local.approveCredit.loanApp.creditScore`

Answer: C

4.A bank has a home loan process containing an 'Approve Credit' activity with a service attached with the same name. During the activity 'Approve Credit', a credit check is done and credit approval is based on the amount to be borrowed and the borrower's credit score. The loan application has five pieces of data: `creditScore`, `newHomeAddress`, `amountToBorrow`, `creditApproved`, and `appraisalPassed`. The data is organized in a complex variable, `loanApp`. What is the minimum output from the 'Approve Credit' service?

- A. `loanApp`
- B. `creditApproved`
- C. `appraisalPassed`
- D. `amountToBorrow`

Answer: B

5.What is the default visibility property for all new controls?

- A. Hidden
- B. Editable
- C. Disabled
- D. Required

Answer: B

6.A developer needs to build the Coach shown in the following Exhibit.

The screenshot shows a web application interface for 'Lombardi Coach'. On the left is a vertical sidebar with a user profile icon and the label 'Coach'. The main content area has a dark blue header with the text 'Lombardi Coach'. Below this is a section titled 'Contact' in a lighter blue header. The form is divided into two columns: 'Personal Information' and 'Contact Details'. The 'Personal Information' column contains 'Name:' with a text input field and 'Birth Date:' with a date picker. The 'Contact Details' column contains 'Phone:' with a text input field, 'Mobile:' with a text input field, and 'Email:' with a text input field. A 'Submit' button is located at the bottom right of the form area.

What is the minimum number of sections the developer needs to create in the Coach?

- A. 1
- B. 2
- C. 3
- D. 4

Answer: D

7.For each section on a Coach, there is an HTML table generated in the background. How are table rows dynamically defined or allocated? Based on the:

- A. number of sections on the Coach.
- B. number of Controls added to each section.
- C. entry specified on the customization property.
- D. Table Override property in the Presentation category.

Answer: B

8.A developer was asked to create a Coach based on the company's form for processing a new employee. For a copy of the company's form, refer to the Exhibit below.

Form #356

Personal Information

Name:
 Street Address:
 City: State: Zip:
 Home Phone: Cell Phone:
 ID Number: _ _ _ _ _

Emergency Contact

Name: Relationship:
 Street Address:
 City: State: Zip:
 Home Phone: Cell Phone:

Employee Availability

Circle one:
 Full-time Part-time 20 hrs/week Part-time 10 hrs/week

Days	Start of Availability	End of Availability
Sunday		
Monday		
Tuesday		
Wednesday		
Thursday		
Friday		
Saturday		

Which simple primitive variable types should be used in this process?

- A. idNumber (Integer), streetAddress (String), state (String), city (String)
- B. idNumber (Integer), streetAddress (Integer), state (String), city (String)
- C. idNumber (String), streetAddress (Address), state (Integer), city (String)
- D. idNumber (String), streetAddress (Address), state (String), city (String)

Answer: A

9. An activity is defined as a conditional activity, and a script that returns a Boolean is written in the text box in the Condition tab. What will happen if the script returns true?

- A. The activity will be skipped.
- B. The activity will be performed.
- C. The activity will be performed if it is added to `tw.system.process.selectedConditionalActivities`.
- D. The activity will be skipped even if the activity is added to `tw.system.process.selectedConditionalActivities`.

Answer: B

10.To add a custom Coach XSL transformation to artifacts in a process application, the XSL file should be added as:

- A. a managed file.
- B. a localization resource.
- C. an installation service.
- D. process application settings.

Answer: A