

# IT-DUMPS Q&A

Accurate study guides, High passing rate!  
IT-dumps provides update free of charge in one year!

**Exam** : **HP0-429**

**Title** : Installing&Supporting  
Standerd HP SAN  
Environments

**Version** : DEMO

**1.Which security mechanism describes hard zoning?**

- A.login authentication
- B.access authorization
- C.network authentication
- D.discovery authorization

**Correct:B**

**2.What can cause a changed hardware path to a connected disk after a switch replacement in an HP-UX environment with multiple B-Series switches? (Select two.)**

- A.Zoning on the new switch is not configured correctly.
- B.Simple Name Service is not copied to the new switch.
- C.Core switch PID format parameter differs from the old one.
- D.New switch has a domain ID which differs from the old one.
- E.Disk (storage controller port) is connected to a different switch port.

**Correct:D E**

**3.An HAFM (High Availability Fabric Manager) appliance must be shut down for maintenance reasons. Which operations are not interrupted?**

- A.logging events
- B.switch monitoring
- C.Fibre Channel traffic
- D.configuration changes

**Correct:C**

**4.You are replacing the active control processor card, CTP2, of an M-series Director switch. Which action is required before removing the CTP?**

- A.Shut down CTP2.
- B.Make CTP2 passive.
- C.Power off the switch.
- D.Shut down the switch.

**Correct:B**

**5.You are adding a new switch to an existing environment. How can you avoid fabric segmentation?**

- A.Assign unique domain IDs to the switches.
- B.Register all domain IDs in the fabric name service.
- C.Set up trusts between switches with different domain IDs.
- D.Assign the same domain IDs to all switches connected by ISLs.

**Correct:A**

**6.What is the maximum number of addressable ports per B-series switch running in Native Address mode?**

- A.8
- B.16
- C.32
- D.64

**Correct:B**

**7.What is the best method to consolidate C-Series SAN islands into a common infrastructure without compromising availability, manageability and network security?**

- A. Zone the SAN.
- B. Configure LSANs.
- C. Implement VSANs.
- D. Link islands with multi-protocol router.

**Correct:C**

**8. Which M-series feature key is required to implement fabric binding and switch binding?**

- A. SANtegrity
- B. Open Trunking
- C. FICON management server
- D. open systems management server

**Correct:A**

**9. You add a switch to a B-series fabric. Its IP address is unknown, so you must use the serial port. Which port attributes must be configured in the terminal emulation in addition to 8 bit, no parity, 1 stop bit?**

- A. 9600baud, no flow control
- B. 19200baud, no flow control
- C. 9600baud, hardware flow control
- D. 19200baud, hardware flow control

**Correct:A**

**10. To solve a customer problem, a remote login to a recently installed High Availability Fabric Manager appliance is required. The customer does not know the username and password. Which factory default login should be used?**

- A. admin / password
- B. Administrator / password
- C. administrator / Password
- D. Administrator / Administrator

**Correct:B**