

**Exam** : HP0-662

Title : NonStop Configuration and

**Planning** 

Version: DEMO

1. Assuming no I/O enclosures, how many electrical branch circuits are needed to provide power fault
tolerance for a six-processor S7x000 system?
A. 2
B. 3
C. 4
D. 6
Answer: D
2. Which items would you expect to see on a network topology diagram? Select TWO.
A. tape devices
B. IP addresses
C. routers
D. disk mapping
E. cable specifications
Answer: BC
3. What allows a customer to track open problem cases through the Web?
A. Scout for NonStop servers
B. Express Notice
C. NonStop Technical Library (NTL)
D. Total Web Support (TWS)
Answer: D
4. Which prediction is NOT produced by TCM?
A. number of processors required
B. number of logical disk volumes
C. network response time
D. processor and disk utilization
Answer: C
5. Which tool simplifies the task of migrating a database from many small disks to a smaller number of

large disks?
A. MEDIACOM
B. ASAP
C. SMF
D. MAPPER
Answer: C
6. DSM/SCM can be used to control customer software. Which program is used to prepare the
software?
A. CNFGINFO
B. ZPHIRNM
C. INITENV
D. INITSTAT
Answer: A
7. To what type of adapter does a default configuration system console connect?
A. E4SA
B. MIOE
C. FESA
D. TRSA
Answer: B
8. Which process needs to be configured to ensure Expand connectivity between two systems?
A. \$znet
B. \$ncp
C. \$expand
D. \$zzatm
Answer: B
9. How many internal disk SCSI controllers are on a PMF CRU?

A. 0
B. 1
C. 2
D. 3
Answer: C
10. Which element is typically included in a separate document in response to a Request for Proposal
(RFP)?
A. software details
B. timescales
C. cost breakdown
D. hardware details
Answer: C
11. Increasing the number of processors in a system
A. provides fault tolerance for the system consoles
B. allows more disk units in group 1 of the system
C. requires a cold load of the system
D. allows more low-pin processes to run in the system
Answer: D
12. Which product can be used to project transaction growths into a resource upgrade timeline?
A. GPA
B. ASAP
C. NSX
D. TCM
Answer: D
13. What is the filename of the SCSI boot code for the G06.08 release?
A. I1000

B. IBOOT
C. 12000
D. ISCSI
Answer: B
14. Which utility is used for routine tape management operations?
A. TAPECOM
B. NSKCOM
C. MEDIACOM
D. TMFCOM
Answer: C
15. Which product requires a manual firmware update using TSM?
A. FESA
B. E4SA
C. SWAN
D. TRSA
Answer: C
16. Which tool has replaced Timbuktu for remote support?
A. Timbuk3
B. Remote Copy
C. Carbon Copy
D. PC Anywhere
Answer: C
17. What is a key difference between TSM low-level link and TSM service connection?
A. service connection communicates only with the MSP
B. service connection shows external devices
C. service connection allows firmware updates

Answer: B
18. Which Windows NT services are required when configuring dial-out on TSM? Select TWO.
A. RPC
B. RAS
C. SAP Agent
D. Network Monitor Agent
E. SNMP
Answer: BE
19. In which volume and subvolume do the hardware configuration files reside?
A. \$system.system
B. \$system.sysnn
C. \$system.zsysconf
D. \$dsmscm.system
Answer: C
20. How can the ServerNet connectivity to CPU 5 be displayed in SCF?
A. INFO SERVERNET 5
B. STATUS SERVERNET \$ZSNET
C. INFO SERVERNET \$ZSNET
D. STATUS SERVERNET 5
Answer: B

D. service connection allows system discovery