

# IT-DUMPS Q&A

Accurate study guides, High passing rate!  
IT-dumps provides update free of charge in one year!

**Exam** : **HP0-S29**

**Title** : Planning and Designing  
ProLiant . Solutions for the  
Enterprise

**Version** : Demo

1. When you are configuring SNMP, what information must you provide to enable the managed system to send alerts to the Central Management Server (CMS)? (Select two.)

- A. community name
- B. community membership
- C. trap origin
- D. trap severity
- E. trap destination

Answer: A,E

2. Which authorization does HP Systems Insight Manager (HP SIM) use to execute CLI commands?

- A. Administrator group
- B. logged-in user
- C. Operator group
- D. User group

Answer: B

3. Your customer is interested in using a full-size, standard PCIe graphics adapter with a ProLiant WS460c G6 Blade Workstation. Which other component must your customer install to use this graphics adapter?

- A. FX 5800 SFF mezzanine card
- B. Graphics Expansion Blade
- C. Microsoft Remote Desktop Protocol (RDP)
- D. Scaleable BladeLink hardware assembly

Answer: B

4. What is used by HP integrated Lights-Out 2 (iLO 2) to improve security? (Select two.)

- A. Secure IPv6
- B. Secure Virtual Password Store
- C. Secure Shell (SSH)
- D. Secure Task Execution (STE)
- E. Secure Sockets Layer (SSL)

Answer: C,E

5. Which statements correctly describe HP FlexNIC technology? (Select two.)

- A. FlexNIC is a virtual NIC contained in a software layer.
- B. The bandwidth of each FlexNIC can be set from 100Mb to 10Gb, in increments of 100Mb.
- C. FlexNICs are available as single-port LAN-on-Motherboard devices on select ProLiant and Integrity server blades.
- D. FlexNICs enable dynamic MAC and WWN addresses to be assigned without changing production LAN and SAN parameters.
- E. Up to four FlexNICs are supported per physical server 10Gb NIC port.

Answer: B,E